



Rechargeable Li-ion Battery Pack

Ver:D

USER MANUAL

SWIT Electronics Co.,Ltd.

Tel:+86-25-85805753
Fax:+86-25-85805296
<http://www.swit.cc>
E-mail: contact@swit.cc

Congratulations on your purchase of this product. Please read this user manual carefully.

Warning

Keep in mind the following precautions to avoid fire and other safety hazards!

- Do not use battery in fire or hot places to prevent overheating, cracking and other hazards.
- Please do not pierce the battery shell or try to open the shell and decompose the battery.
- Do not use battery beyond charge, discharge and storage environment temperature.
- Do not charge the battery in the car or in direct sunlight.
- Do not use damaged battery.
- Do not squeeze the battery shell which may cause physical damage.
- Make sure the power-consuming equipment(s) meet the battery specifications.
- Use SWIT charger or SWIT recommended charger to charge the battery to avoid overheating or beak.
- Keep out of the reach of children.

Caution

- Fully charged battery will discharge naturally and please use it as soon as it gets charged.
- The battery may become warm in use or while being charged. This is normal.
- Never expose the battery to temperature above 60°C.
- Keep the battery terminals clean and never short-circuit the battery terminals.
- When stored for a long time, please keep the battery power between 50% and 90%, please do not save it for a long time after it has run out of power.

Features

- High performance rechargeable lithium ion battery, no memory effect.
- 4-step LED power indicator.
- Build-in multiple protective circuit design.
- D-tap DC output, to power the camera and other equipment simultaneously.

Charging

- The battery pack should be charged within a temperature range of 0~40°C, but it is suggested charge the battery within 10~30°C for better performance.

Discharging

- At low temperature, the battery internal resistance will increase, which may lead to automatically cut off if the load is heavy.
- The battery can discharge at a temperature range of -20°C ~50°C, but it is suggested to discharge at a temperature range of -10~40°C for the best performance of the battery.
- The battery will automatically cut off power to protect itself when current or temperature is abnormal. Please remove the battery, and it will restore after 60 seconds' standing. If the battery overheats, place it in a cool place and the battery will automatically recover after cooling.
- If the voltage is too high because of the charger or other equipments, please discharge the battery to decrease the voltage then it will be restored automatically.

Specification

Model			S-8082S	S-8110S	S-8113A	S-8113S
Mount			V mount	V mount	Gold mount	V mount
Nominal Voltage			14.4V			
Capacity			95Wh,6.6Ah	146Wh,10.2Ah	160Wh,11.1Ah	
Interface Parameters	Electrodes	Output	150W,12A		200W,16A	
		Input	16.8V,4A Max	16.8V,5A Max	16.8V,8A Max	
	D-TAP	Output	120W,10A			
		Input	16.8V,4A Max	16.8V,5A Max	16.8V,8A Max	
	In total	Output	150W		200W	
Dimension			134×88×52mm	165×90×51mm	165×90×53mm	165×90×51mm
Mass			0.71kg	0.94kg	0.98kg	0.98kg
Charging temperature			0～40℃（10～30℃ recommended）			
Discharging temperature			-20℃～50℃（-10～40℃ recommended）			

Model			S-8180S	S-8183A+	S-8183S+	S-8073N
Mount			V mount	Gold mount	V mount	NP-1
Nominal Voltage			14.4V			
Capacity			220Wh,15.3Ah	270Wh,18.75Ah		73Wh,5.1Ah
Interface Parameters	Electrodes	Output	200W,16A	250W,20A		66W,5.5A
		Input	16.8V,8A Max			16.8V,3A
	D-TAP	Output	120W,10A			66W,5.5A
		Input	16.8V,8A Max			16.8V,3A
	In total	Output	200W	250W		66W
	Dimension			165×90×66mm	165×90×68mm	165×90×66mm
Mass			1.28kg	1.37kg	1.37kg	0.45kg
Charging temperature			0～40℃（10～30℃ recommended）			
Discharging temperature			-20℃～50℃（-10～40℃ recommended）			